

DOP: Spaandex EN 312 P3							
1. Type of materiel:	Particleboard acc. to EN 312 P3						
2. Unique identification code of the product-type	Spaandex EN 312 P3						
3. Intended use	Non-loadbearing for use in humid conditions						
4. Manufactured at	Kronospan ApS Novopan Træindustri Fabriksvej 2, Pindstrup DK-8550 Ryomgård						
5. System of AVCP.	AVCP 2						
6. Notified Body	Dancert A/S Gregersensvej 4 DK-2630 Taastrup						
7. Declared performance *: EN 321	Thickness [mm]	>10-13	>13-20	>20-25	>25-32	32-38	EN 1398 6:20 04 EN 312: 2010
	Bending strength [N/mm ²]	≥ 15	≥ 14	≥ 12	≥ 11	≥ 9	
	Modulus of elasticity [N/mm ²]	≥ 2050	≥ 1950	≥ 1850	≥ 1700	≥ 1500	
	Internal bond [N/mm ²]	≥ 0,45	≥ 0,45	≥ 0,40	≥ 0,35	≥ 0,30	
	Int.bond cycl. test [N/mm ²]	≤ 17	≤ 14	≤ 13	≤ 13	≥ 0,09	
	Swelling 24 h (%)	≥ 0,15	≥ 0,13	≥ 0,12	≥ 0,10	12	
	Swelling cyclic test [%]	≤ 14	≤ 13	≤ 12	≤ 11	12	
	Formaldehyde [mg/100g v. 6,5% fugt]	≤ 8	≤ 8	≤ 8	≤ 8	≤ 8	
	Reaction to fire	Ds2-d0	Ds2-d0	Ds2-d0	Ds2-d0	Ds2-d0	

The performance of the product identified is in conformity with the declared performances.



KRONOSPAN ApS
PINDSTRUP
8550 Ryomgård

Henrik Skovbo, laboratorie- og kvalitetschef

Pindstrup d. 09-05-2022